

AnaCom's smaller-sized mBUCs provide the high output power and high reliability of an AnaCom BUC in a compact package suited for use with most mobile and fly-away antennas. mBUCs are designed for continuous outdoor duty in all types of harsh environments. Ideally suited for SCPC, MCPC, DAMA, TDMA, and VoIP applications and designed to interface with any L-band modem, the mBUC may be used in a wide variety of communication networks.

AnaCom's mBUC features web-based and command-line access to Monitor and Control functions accessible via Ethernet, FSK, Telnet, RS-232- and RS-485, and device monitoring over SNMP.

## Features

- ✓ Built in test capabilities for improved maintainability and reduced dependence on external test equipment
- ✓ No indoor RF equipment is needed
- ✓ Superior phase noise
- ✓ Flexible, universal DC power supply (AC optional)

## Built In Test Capability

To improve and simplify maintenance routines, an external terminal (or computer) can be connected to monitor a number of critical parameters without use of additional test equipment. These include:

- ✓ Transmitter power output level
- ✓ TX IF level
- ✓ Power supply voltages
- ✓ TX synthesizer loop voltages
- ✓ Internal Temperature
- ✓ Alarm Details

Controllable functions from the terminal include:

- ✓ TX On/Off
- ✓ TX Gain

## Benefits

- ✓ "Last Touch" controls allow for remote configuration or local (*manual*) configuration
- ✓ Flash memory means that the mBUC always powers up with exactly the same operating conditions as when it lost power (*or was shut down*)
- ✓ Comprehensive maintenance features for operational effectiveness and minimum outages.
- ✓ Simple installation.

## Comprehensive Monitor & Control

The mBUC's Monitor & Control feature allows you to monitor and control the mBUC on the same M&C bus with most indoor equipment such as modems and multiplexers. The Monitor & Control system can be used in combination with the unit's internal metering function to monitor operational parameters.

The M&C can be accessed remotely via-

- |                        |                        |
|------------------------|------------------------|
| Ethernet protocols:    | Serial protocols:      |
| ✓ Internal Webpage     | ✓ RS-232               |
| ✓ Telnet               | ✓ RS-485               |
| ✓ SNMP                 | ✓ AnaCom Supervisor 10 |
| ✓ AnaCom Supervisor 10 |                        |

## Compact, Functional Design

The upconverter, power amplifier, monitor and control and power supply are included in a single enclosure. The only cabling required to the indoor equipment are IF and power. An optional ovenized, high stability crystal oscillator can be used to lock the TX synthesizer. Additional temperature and aging compensation are provided by an onboard microprocessor.



# mBUC

Ku-Band Series

## SPECIFICATIONS

	<b>4W</b>	<b>8W</b>	<b>16W</b>	<b>20W</b>	<b>25W</b>	<b>32W</b>	<b>40W</b>	
1 dB COMPRESSION POINT (dBm)	36	39	42	43	44	45	46	
TX GAIN	61	64	67	68	69	70	71	
TX GAIN RANGE	20 dB variable in 1 dB steps via M&C							
TX LEVEL FLATNESS	3 dBp-p max / 500 MHz							
TX GAIN OVER TEMPERATURE	+/- 1.5 dB max							
TX INPUT IF FREQUENCY	Ku = 950 to 1450 MHz	EKu = 950 to 1450 MHz	SEKu = 950 to 1,700 MHz					
TX INPUT IF IMPEDANCE	50 ohms (75 ohms optional)							
TX INPUT IF LEVEL	-25 dBm for rated output with nominal gain							
TX L.O.	Ku = 13.050 GHz	Eku = 12.800 GHz	SEKu = 12.800 GHz					
TX OUTPUT FREQUENCY	Ku = 14.0 to 14.50 GHz	Eku = 13.75 to 14.25 GHz	SEKu = 13.75 to 14.50 GHz					
TX FREQUENCY STEP SIZE	1 MHz M&C controlled							
TX PHASE NOISE	-60 dBc/Hz max @ 100Hz -90 dBc/Hz max @ 100KHz	70 dBc/Hz max @ 1KHz -100 dBc/Hz max @ 1MHz	-80 dBc/Hz max @ 10KHz					
INTERMOD	-25 dBc max (2 carriers, each 6dB backoff from P1dB rating)							
SPURIOUS	-55 dBc max out of band							
REFERENCE	Requirements	Provided on TXIF line by L-band modem						
	FREQUENCY	10 MHz (sine-wave)						
	INPUT POWER	-5 to +5 dBm (at input port)						
	PHASE NOISE	-125 dBc/Hz max @ 100Hz -135 dBc/Hz max @ 1KHz -140 dBc/Hz max @ 10KHz						
	INTERNAL REFERENCE OPTION	10 <sup>-8</sup> over rated temperature						
SYSTEM	ALARM RELAYS	FORM C for Summary Alarm; Isolated						
	POWER	4W, 8W 16W - 40W	24V DC 48V DC	optional external AC				
	M&C	SNMP, HTTP, Telnet	Ethernet, RS-232, RS-485					
ENVIRONMENTAL	TEMPERATURE	-50 to +55°C operational -50 to +75°C storage						
	HUMIDITY	95% at 45C						
	ALTITUDE	6500 meters (21,500 ft) max						
	RAIN	20 inches per hour						
	WIND	150 miles per hour						
	VIBRATION	1.0 g random operational, 2.5 g random survival						
	SHOCK	10 g operational, 40 g survival						
POWER & DIMENSIONS		<b>4W</b>	<b>8W</b>	<b>16W</b>	<b>20W</b>	<b>25W</b>	<b>32W</b>	<b>40W</b>
	TYPICAL POWER CONSUMPTION (VA)	45	111	183	230	237	254	360
	PRIME POWER RECOMMENDATION	90	220	366	460	474	508	720
	WEIGHT:				13 lbs. 5.9 kg.			
	BUC SIZE:				10.95" x 7.08" x 4" 278mm x 180mm x 98mm			

\*all specifications subject to change

06/10/19

3297209



Phone: +1 408 519 2062  
www.anacominc.com

Fax: +1 408 519 2063